



Control Circuit Protection Supplementary Protectors, AC/DC Product Range

5SY5 70 mm mounting depth

Features

- U_n : 230/400 V, 50-60 Hz, 220 V DC per pole, applicable in networks up to: 250/440 V AC
- 220 V DC: 1-pole
- 440 V DC: 2-pole
- Standards: EN 60 898-1, DIN VDE 0641 Part 11, IEC 60 898
- Additional components can be retrofitted.
- **Devices do not comply with UL1077**

Selection and ordering data

	I_n	MW ¹⁾	Characteristic B		Characteristic C		Weight 1 item	Pack. unit	
			Order No.	List Price \$ 1 item	Order No.	List Price \$ 1 item			
1-pole									
	A	1	-	-	5SY5 114-7	98.00	0.147	12	
			0.3	-	5SY5 105-7	98.00			
			0.5	-	5SY5 101-7	98.00			
			1	-	5SY5 115-7	98.00			
			1.6	-	5SY5 102-7	98.00			
			2	-	5SY5 103-7	98.00			
			3	-	5SY5 104-7	98.00			
			4	-	5SY5 106-6	98.00			
			6	5SY5 106-6	98.00	5SY5 106-7			98.00
			8	-	5SY5 108-7	98.00			
			10	5SY5 110-6	98.00	5SY5 110-7			98.00
			13	5SY5 113-6	98.00	5SY5 113-7			98.00
			16	5SY5 116-6	98.00	5SY5 116-7			98.00
			20	5SY5 120-6	98.00	5SY5 120-7			98.00
			25	5SY5 125-6	98.00	5SY5 125-7			98.00
32 ¹⁾	5SY5 132-6	98.00	5SY5 132-7	98.00					
40	5SY5 140-6	114.00	5SY5 140-7	114.00					
50	5SY5 150-6	130.00	5SY5 150-7	130.00					
63	5SY5 163-6	146.00	5SY5 163-7	146.00					
2-pole									
	A	2	-	-	5SY5 214-7	196.00	0.304	6	
			0.3	-	5SY5 205-7	196.00			
			0.5	-	5SY5 201-7	196.00			
			1	-	5SY5 215-7	196.00			
			1.6	-	5SY5 202-7	196.00			
			2	-	5SY5 203-7	196.00			
			3	-	5SY5 204-7	196.00			
			4	-	5SY5 206-6	196.00			
			6	5SY5 206-6	196.00	5SY5 206-7			196.00
			8	-	5SY5 208-7	196.00			
			10	5SY5 210-6	196.00	5SY5 210-7			196.00
			13	5SY5 213-6	196.00	5SY5 213-7			196.00
			16	5SY5 216-6	196.00	5SY5 216-7			196.00
			20	5SY5 220-6	196.00	5SY5 220-7			196.00
			25	5SY5 225-6	196.00	5SY5 225-7			196.00
32	5SY5 232-6	196.00	5SY5 232-7	196.00					
40	5SY5 240-6	212.00	5SY5 240-7	212.00					
50	5SY5 250-6	228.00	5SY5 250-7	228.00					
63	5SY5 263-6	244.00	5SY5 263-7	244.00					

1) MW = modular width of 18 mm
Depth 70 mm = device mounting depth of 70 mm